

VENLOCM-EVAB05

PRODUCT IDENTIFICATION

- **Chemical Name:** EVA Black Masterbatch
- **Physical Form:** Black Masterbatch

HAF type black masterbatch concentrate, PE support, with medium high jetness and high tint strenght.VENLOCM-EVAB05 finds app. in injection molding, blow molding,compounding, extrusion pipes and wire&cable. Suitable for coloring recycled material. Designed to easy dillution and homogeneous mixing and for direct addition by automatic dispensers or pre-mixing such as injection industry,compounding, extrusion pipes, extrusion wire & cable, blown film, textile spinning,cast film.

SPECIFICATION

| Properties | Test Methods | Units | Values |
|--------------------|--------------|----------------------|-----------|
| Density | ISO 1183 | gr / cm ³ | 1.17±0.01 |
| Moisture Content | INTERNAL | % | <0,4 |
| TGA (Carbon Black) | INTERNAL | % | 40 |
| Heat Stability | ISO 75 | °C | 300 |
| Light Stability | ISO 4892 | Blue Scale | 8 |
| Filler | - | - | No |
| Carrier | - | - | EVA |

PACKAGING & STORAGE

- Packaging: 1 pallet is 1250 kg in octabin.
- VENLOCM-EVAB05 should be stored in a manner that avoids direct exposure to sunlight and heat(T<30°C).This compound should be used within 6 months after its production date.

IMPORTANT NOTICE

Please read the Material Safety Data Sheet (MSDS) carefully before using this product.

