

VENLOMC-DBTDL

PRODUCT IDENTIFICATION

- **Chemical Name:** Metal Catalyst DBTDL
- **Physical Form:** Pale Yellow Liquid
- **CAS Number:** 77-58-7

VENLOMC-DBTDL is a premium quality dibutyltin dilaurate catalyst for foaming polyurethane. Dibutyltin dilaurate is widely used in the manufacture of polyether and polyester based urethane polymers and as a catalyst in the polymerisation of adhesives and urethane sealants.

SPECIFICATION

Properties	Test Methods	Units	Values
Wt. Tin	-	%	18.4
Specific Gravity (25°C)	EN ISO 1183-1	g/cm ³	1.045
Refractive Index (N _D ²⁵)	-	n	1.467
Viscosity	ASTM D-5125	cps	34
Freezing Point	-	°C	8
Flash Point	ASTM D92-18	°C	293

APPLICATIONS

- VENLOMC-DBTDL catalyzes esterification reactions, transesterification reactions and polycondensation reactions and has become the industry standard for coatings, adhesives, solvents and elastomers.

PACKAGING & STORAGE

- Packaging: 1 pallet is 816 kg Pallet (4 Drums*204 kg).
- VENLOMC-DBTDL should be stored in a manner that avoids direct exposure to sunlight and heat (T < 30°C). This compound should be used within 6 months after its production date.

IMPORTANT NOTICE

Please read the Material Safety Data Sheet (MSDS) carefully before using this product.

